



Quality and reliability is our tradition

KYORITSU JAPAN

www.kew-ltd.co.jp

www.kyoritsu-instrumenti.com

www.melcobuda.co.yu

◀ Diferencijalna merna kljesta

MODEL **2413F**

- Extra velika merna kljesta su najbolje rešenje za obuhvatanje odjednom 3 faza -3-4 kabla zajedno za praćenje merenje nivoa stetnih struja.
- Frekvencijski filter –prekidac eliminiše efekte spoljnih harmonika.
- Pik I hold funkcija.
- Analogni izlazni terminal (za snimanje dugorocnih merenja).

Φ68	MAX AC1000A	Resolution 0.1mA	OUT PUT
PEAK 10/100ms	Filter		



CE

AC A (50/60Hz)	200mA/2/20/200A/1000A ±1.5%rdg±2dgt (200mA/2/20A) ±2%rdg±2dgt (200A 0~500A) ±5.5%rdg (501~1000A)
AC A (WIDE)	200mA/2/20/200/1000A ±1%rdg±2dgt [50/60Hz], ±3%rdg±2dgt [40Hz~1kHz] (200mA/2/20A) ±1.5%rdg±2dgt [50/60Hz], ±3.5%rdg±2dgt [40Hz~1kHz] (200A/0~500A) ±5%rdg [50/60Hz], ±10%rdg [40Hz~1kHz] (501~1000A)
Max mereni kabal Fi	Ø68mm max.
Sigurnosni Standard	IEC61010-1 CAT.III 300V IEC61010-2-032
Effekt spoljnog magnetnog polja Ø15mm 100A	10mA AC max.
Frekvencijski opseg	40Hz~1kHz
Izlaz	AC/DC 200mV against 2000 count
Mx naponsko preopterećenje	3000V AC do 1 minute

Napajanje	6F22(9V) × 1 kom
Dimenzije	250(L) × 130(W) × 50(D)mm
Tezina	570g approx.
dodatci	9064(specijalno zaštitno kuciste) 6F22 × 1 Instruction Manual
Posebno se narucuje	7073 (2 smerni izalzni kablovi)