

# DIGITALNA MERNNA KLJESTA KEW SNAP SERIJA



2040



2046R



2055



2056R

- 600Ampera i 1000Ampera Merna Kljesta
- Velicina merenog provodnika: 33mm / 40mm
- LCD prikazuje 6000 brojeva I ima Bar graf(simulacija analog.)
- Dvostruko ojacano kuciste obezbedjuje komforan i prijatan osecaj pri drzanju u ruci.
- AC/DC struja I napon merenje zatim merenje :
- Otpornosti, Kapaciteta, Diode, Frekvencija I Temperatura
- NCV(beskontaktna reg.napona), MIN / MAX vrednosti
- Safety Standard IEC61010-1 CAT. IV 600V



2046R  
2056R

MODEL	2040 (AC)	2046R (AC/DC, Realni RMS)	2055 (AC/DC)	2056R (AC/DC, Realni RMS)
AC A	0~600.0A 1.5%rdg±5dgt(50/60Hz) 3.5%rdg±8dgt(40~400Hz)	0~600.0A 2.0%rdg±5dgt(50/60Hz) 3.5%rdg±5dgt(40~400Hz)	0~600.0/1000A 1.5%rdg±4dgt(50/60Hz) 3%rdg±5dgt(40~400Hz)	0~600.0/1000A 2.0%rdg±5dgt(50/60Hz) 3.5%rdg±5dgt(40~400Hz)
AC V	6/60/600V Automatsko prebacivanje opsega 1.3%±4dgt(50/60Hz) 3%rdg±5dgt(40~400Hz)	6/60/600V Automatsko prebacivanje opsega 1.5 %±4dgt(50/60Hz) 3.5%rdg±5dgt(40~400Hz)	6/60/600V Automatsko prebacivanje opsega 1.3%±4dgt(50/60Hz) 3%rdg±5dgt(40~400Hz)	6/60/600V Automatsko prebacivanje opsega 1.5%±4dgt(50/60Hz) 3.5%rdg±5dgt(40~400Hz)
DC A		0~600.0A 1.5 %rdg±5dgt	0~600.0/1000A 1.5%rdg±5dgt	0~600.0/1000A 1.5%rdg±5dgt
DC V	600m/6/60/600V Automatsko prebacivanje opsega 1.0%±3dgt	600m/6/60/600V Automatsko prebacivanje opsega 1.0%±3dgt	600m/6/60/600V Automatsko prebacivanje opsega 1.0%±3dgt	600m/6/60/600V Automatsko prebacivanje opsega 1.0%±3dgt
Frequency /DUTY	10/100/1k/10kHz(Automatsko prebacivanje opsega)/0.1 99.9%			
Ω	600/6k/60k/600k/6M/60MΩ( Automatsko prebacivanje opsega) 1%±5dgt(600~6M)/ 5%±8dgt(60M)			
Zvuk kontinuiteta	Zvucni signal na 100Ω			
Vel.provodnika	φ33mm		φ40mm	
Provera Diode	•	•	•	•
Merenje kapaciteta		40n/400n/4μ/40μF Automatsko prebacivanje opsega		40n/400n/4μ/40μF (Automatsko prebacivanje opsega)
Temperatura		•		•
Mem.poslednje merene vrednosti-hold	•	•	•	•
Mem. Vrsne vrednosti- Peak Hold		•		•
Max/Min	•	•	•	•
Bar graf	•	•	•	•
NCV*	•	•	•	•
Pozadinsko osvetljenje LCDa		•	•	•
Max napon trenutni	6880V AC do 5 sekundi			
Sigurnosni Standard	IEC61010-1 CAT. 600V, IEC 61010-031, IEC 61010-2-032, IEC 61326			
baterije	Alkaline R03 (1.5V)(AAA) x 2			
Dimenzije	243(L) x 77(W) x 36(D) mm		254(L) x 82(W) x 36(D) mm	
Tezina	300g		310g	
dodatci	Test kablovi Zastit.torbica Uputstvo za rukovanje	Test kablovi Zastit.torbica Uputstvo za rukovanje Temperature probe senzor	Test kablovi Zastit.torbica Uputstvo za rukovanje	Test kablovi Zastit.torbica Uputstvo za rukovanje Temperature probe sensor

**\*Moze da registruje postojanje napona na merenoj zici beskontaktno !!!**

**Melco Buda d.o.o.**

- kancelarija u Beogradu: Jurija Gagarina br.257/II sprat/12 , 11070 Novi Beograd  
tel: 011/6277-410, mob: 065/311-9422

e mail: [office-beograd@melcobuda.co.rs](mailto:office-beograd@melcobuda.co.rs) , [budimir.melcobuda@gmail.com](mailto:budimir.melcobuda@gmail.com)  
[www.melcobuda.co.rs](http://www.melcobuda.co.rs) , [www.kyoritsu-instrumenti.com](http://www.kyoritsu-instrumenti.com) , [www.termovizija.com](http://www.termovizija.com) , [www.hioki-instrumenti.com](http://www.hioki-instrumenti.com)

- kancelarija u Despotovcu: Saveza Boraca br.7, 35213 Despotovac, Srbija  
tel:035/612 916, faks:035/613 319, mob. 063/8003370  
e mail: [office@kyoritsu-instrumenti.com](mailto:office@kyoritsu-instrumenti.com) , [office@melcobuda.co.rs](mailto:office@melcobuda.co.rs)

- Germany address: Quer strasse 18 Offenbach